



HelarcoUS VP65

#222VP65

#LD12VP65091020



Notes:

The VP65 12ga lead, steel, ITX shot column wad (static wad, no cushion). Designed for game loads. Best use is in the 3" 12-gauge hull. Some loads for the VP65 will fit into 2.75" hulls. Best loads are 1-1/2 lead, 1-1/4 to 1-3/8 ITX™ shot, and 1-ounce (#3) steel shot loads.

The VP65 is 1.665" long with shotcup depth of 1.410" and four 45-degree angled slits (1.260" in length). The VP65 has a tapered interior with wall thickness running near the mouth at .035" to a base side thickness of .060". The gas seal is .730" diameter and .150" deep. The VP65 wad will load in 2.75" hulls of most all types, depending upon the powder called for in the data. When utilized in 3" gauge hull, a gas seal or nitro card may be used.

Technical Specs:

Gas seal:	Single-step recessed obturator
Shotcup body:	1.665"
Shotcup depth:	1.410"
Seal to cup bottom:	N/A
Shotcup type:	Four-petal, 45-degree angled slit
Number of slits:	4
Maximum load amount:	1 1/2 oz. (lead), 1 1/8 oz. (steel)

Lead Loads

ID #	Ref.#	Ga	Length	Hull	Primer	Powder	Gr.	Wad	OS Card	Oz.	Shot	PSI	FPS	Other	Crimp	Notes
90518	881	12	2.75	Fiocchi	Fio-616	Blue Dot	36.0	VP65 + 18CW20		1 3/8	Lead #6	11200	1340	Mica dust wad	Fold	
90518	882	12	2.75	Fiocchi	Fio-616	Blue Dot	37.0	VP65 + 18CW20		1 3/8	Lead #6	11400	1360	Mica dust wad	Fold	
90519	886	12	2.75	Fiocchi	Fio-616	HS-6	29.0	BPGS + VP65		1 3/8	Lead #6	11000	1245	Mica dust wad	Fold	
90519	885	12	2.75	Fiocchi	Fio-616	SR-4756	31.0	VP65 + 18CW20		1 3/8	Lead #6	10900	1250	Mica dust wad	Fold	
90518	883	12	2.75	Fiocchi	Fio-616	SR-4756	31.6	VP65 + 18CW20		1 3/8	Lead #6	11300	1325	Mica dust wad	Fold	
90519	887	12	3.00	Fiocchi	Fio-616	Longshot	33.0	X12X + VP65 + 14CW20		1 1/4	Lead #6	11000	1430	Mica dust wad	Fold	

Steel Loads

ID #	Ref.#	Ga	Length	Hull	Primer	Powder	Gr.	Wad	OS Card	Oz.	Shot	PSI	FPS	Other	Crimp	Notes
90615	969	12	2.75	Fiocchi	Fio-616	SR-4756	28.0	VP65	OS12	1	Steel #3	10300	1270	Mica dust wad	Fold	
91118	1576	12	2.75	Rio	Rio-209	SR-4756	30.0	VP65		1	Steel #3	9600	1260	Mica dust wad	Fold	Fit+
90615	972	12	2.75	Fiocchi	Fio-616	Steel	36.0	VP65		1	Steel #3	10800	1570	Mica dust wad	Fold	
91118	1577	12	2.75	Rio	Rio-209	Steel	37.0	VP65		1	Steel #3	7800	1395	Mica dust wad	Fold	Fit+
90519	889	12	3.00	Fiocchi	Fio-616	Steel	42.0	VP65		1	Steel #2	10900	1710	Mica dust wad	Fold	

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. FOLLOW LOADING DATA AND WARNINGS OF RELOADING EXACTLY. WE DISCLAIM ANY LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER YOUR LOADING PRACTICES AND METHODS. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. THIS PRODUCT MUST NOT BE USED IN GUNS HAVING DAMASCUS OR TWIST STEEL BARRELS. KNOW WHAT IS BEHIND YOUR. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS". SEE PRODUCT-SPECIFIC WARNINGS ON PRODUCT PACKAGING.