



BPI LOAD GUIDE:

SPHEROTUNGSTEN-15 & 18

WWW.BALLISTICPRODUCTS.COM

SpheroTungsten Original-15 Shot is density verified at 15 grams/cc. It is a unique pellet formulation consisting mainly of tungsten, but also contains iron, copper, and nickel alloys. It is dense and lethal on turkeys, ducks, geese, and just about any other game birds. The Curmudgeon uses SpheroTungsten #7 D15 on game birds in his light 28-gauge. The birds immediately drop from the sky.

- 15 g/cc (27% denser than magnum lead)
- Tungsten/Iron/Copper/Nickel
- USFWS approved non-toxic
- Patented

SpheroTungsten Super Max-18 Shot is the world's densest shot material. This shot is not plated, but it appears to be because of the smooth, lustrous finish. It is finely polished to enhance surface finish and reduce abrasiveness. The result is a rich, fine appearance. Many adjectives can apply to this shot, but we just call it perfect.

This is the densest shot our ballistic lab has ever tested. Super Max-18 shot is manufactured by the world's premier non-toxic shot manufacturer and it is used and tested by the greatest cartridge manufacturers in the U.S. and around the world. This global reputation for excellence means that each production lot is certified to be the finest and most consistent shot on the planet. SpheroTungsten technology creates Super Max-18 shot to maximum density of 18 grams per cubic centimeter. The intellectual property of the manufacturing process of this nearly perfect sphere is protected by a U.S. patent.

Loading: SpheroTungsten Super Max can be loaded like any other 18.0 density tungsten super shot.

- 18 g/cc (almost 40% denser than magnum lead)
- USFWS approved

*A note on industry manufacturing standards: Unlike steel shot, pure tungsten is so very hard that it cannot be formed to absolute precision. As a result, industry standards allow for slight diameter variation between lots. This can account for variations in pellet count per ounce. Overall density is measured as an aggregate density, which is based on all pieces measured in each individual sample test. Lot-to-lot counts may fluctuate in small increments.



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER	PSI	FPS
10-GAUGE • 3-1/2" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180413-9952	10	Federal	Fed209A	Steel	34.0		TPS1035	(3)14FW12 in base	OS10	2	875.0	ST Original-15		8185	1125
180716-10089	10	Federal	Fed209A	Steel	36.0		TPS1035	(4)14FW12 in base		2	875.0	ST Original-15		6000	1100
12-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180314-9917	12	Cheddite	Ched209	Pro Reach	33.0		MG42	(2) 14FW20 in base	OS12	1	437.5	ST Original-15 #7		8840	1540
230314-11763	12	Cheddite	Ched209	Pro Reach	35.0		BP1253	14CW20 + 18CW20 in base		1	437.5	ST Original-15 #7		8600	1560
180802-10115	12	Federal FB	Fed209A	Longshot	37.0	FS12	LBC30 (slit)	14FW20 in base	OS12	1	437.5	ST Original-15 #7		10830	1640
180709-10073	12	Federal FB	Fed209A	Pro Reach	35.0		MG42	(2) 14FW20 in base		1	437.5	ST Original-15 #7		8940	1600
180119-9789	12	Federal IBW	Fed209A	Pro Reach	35.0		MG42	(2) 14FW20 in base	OS12	1	437.5	ST Original-15 #7		10395	1615
180212-9837	12	Federal IBW	Fed209A	Pro Reach	35.0	BPGS	BP12 (slit)	(2) 18CW20 in base		1	437.5	ST Original-15 #7		9140	1570
180724-10098	12	Fiocchi	Fio616	Longshot	35.0		CSD078 (slit)	14FW20 in base	OS12	1	437.5	ST Original-15 #7		8360	1565
180724-10097	12	Fiocchi	Fio616	Unique	30.0		CSD078 (slit)	14FW20 in base	OS12	1	437.5	ST Original-15 #7		10410	1530
230323-11782	12	Cheddite	Ched209 HOT	Longshot	31.0		BP1253	14CW20 in base		1 1/8	492.2	ST Original-15 #7		6708	1356
221221-11646.2	12	Cheddite	Ched209	Longshot	34.5		BP1253	14CW20 in base		1 1/8	492.2	ST Original-15 #7		11100	1507
230421-11785	12	Cheddite	Ched209	Longshot	31.0		BP1253	14FW20 in base		1 1/4	546.9	ST Original-15 #7	18 gr BSB	9345	1376
230421-11784	12	Cheddite	Ched209 HOT	Longshot	31.0		BP1253	14FW20 in base		1 1/4	546.9	ST Original-15 #7	18 gr BSB	10245	1401
230509-11831	12	Federal PB	Fed209A	Longshot	32.0		BP1251			1 1/4	546.9	ST Original-15 #7	18 gr BSB	7533	1353
230509-11832A	12	Federal PB	Fed209A	Longshot	34.0		BP1251			1 1/4	546.9	ST Original-15 #7	18 gr BSB	11000	1480
10947	12	Fiocchi	Fio616	Longshot	29.2		CLBC (slit)	14CW20 in base	OS12	1 1/4	546.9	ST Original-15 #7		8700	1305
210312-11122	12	Rio	Rlo209	HS-6	28.2		CLBC (slit)	(2) 14FW20 in base	OS12	1 1/2	656.3	ST Original-15 #7		8815	1085
12-GAUGE • 3" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
221221-11659	12	Cheddite	Ched209	Pro Reach	29.0	N712	BP1253			1 5/8	710.9	ST Original-15 #7		11000	1201
180323-9932	12	Cheddite	Ched209	Blue Dot	28.0	NC12	MG42			1 7/8	820.3	ST Original-15 #7		7230	1000
180326-9933	12	Cheddite	Ched209	IMR Blue	30.0	X12X	MG42			1 7/8	820.3	ST Original-15 #7		9540	1080
12-GAUGE • 3-1/2" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180319-9922	12	Cheddite	Ched209	Steel	34.0	FS12	CSD118 (slit)		OS12	2	875.0	ST Original-15 #7		10185	1175
16-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180319-9924	16	Cheddite	Ched209	Longshot	28.0		CSD16 (slit)	(3) 14CW20 in base		3/4	328.1	ST Original-15 #7		8300	1560



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER	PSI	FPS
16-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP (CONTINUED)															
180925-10646	16	Fiocchi	Fio616	Longshot	30.0		CSD16 (slit)	(3) 14CW20 in base	OS16	3/4	328.1	ST Original-15 #7		6540	1500
180911-10629	16	Fiocchi	Fio616	Pro Reach	25.0		CSD16 (slit)	(3) 14CW20 + 18FW20 in base		3/4	328.1	ST Original-15 #7		4915	1330
180119-9801	16	Cheddite	Ched209	Pro Reach	22.0	NC16	CSD16 (slit)	(2) 14FW20 in base	OS16	1	437.5	ST Original-15 #7		8135	1285
180809-10119	16	Fiocchi	Fio616	Pro Reach	25.0		CSD16 (slit)	(2) 14FW12 in base	OS16	1	437.5	ST Original-15 #7		7680	1365
11531	16	Cheddite	Ched209	Blue Dot	22.2		BP1680 (slit)	(2) 14FW20 + 18CW28 in base	OS16	1 1/8	492.2	ST Original-15 #7		6198	1017
11532	16	Cheddite	Ched209	Blue Dot	24.6		BP1680 (slit)	(2) 14FW20 + 18CW28 in base	OS16	1 1/8	492.2	ST Original-15 #7		7343	1111
11541	16	Fiocchi	Fio616	Blue Dot	26.0		BP1680 (slit)	(2) 14FW20 + 18CW28 in base	OS16	1 1/8	492.2	ST Original-15 #7		10900	1223
20-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180222-9871	20	Cheddite	Ched209	Longshot	22.0	NC20	CSD20 (slit)	(3) 14FW20 in base	OS20	3/4	328.1	ST Original-15 #7		10200	1425
10960	20	Cheddite	Ched209	Longshot	18.0		TPS2044 (slit)	(5) 18CW28 in base	OS20	7/8	382.8	ST Original-15 #7		10135	1225
10961	20	Fiocchi	Fio616	IMR Blue	22.0		CSD20 (slit)	(5) 18CW28 in base	OS20	7/8	382.8	ST Original-15 #7		8040	1110
180726-10113	20	Fiocchi	Fio616	Lil' Gun	35.0		CSD20 (slit)	(2) 14FW20 in base	OS20	1	437.5	ST Original-15 #7		6000	1300
180221-9869	20	Cheddite	Ched209	Lil' Gun	35.0		CSD20 (slit)	(2) 14C28 in base		1 1/8	492.2	ST Original-15 #7		10535	1355
191226-10712	20	Fiocchi	Fio616	Lil' Gun	34.0		TPS2044 (slit)	(4) 18CW28 in base		1 1/8	492.2	ST Original-15 #7		9085	1305
180809-10117	20	Fiocchi	Fio616	Lil' Gun	35.0		CSD20 (slit)	14C28 in base		1 1/8	492.2	ST Original-15 #7		10785	1375
10949	20	Fiocchi	Fio616	Lil' Gun	32.5		TPS2044 (slit)	(3) 18CW28 in base		1 1/4	546.9	ST Original-15 #7		9875	1230
20-GAUGE • 3" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180412-9943	20	Cheddite	Ched209	Lil' Gun	32.0		CSD203 (slit)	(2) 14CW28 in base	OS20	1 1/8	492.2	ST Original-15 #7		8220	1255
11589	20	Cheddite	Ched209 HOT	Lil' Gun	28.0	N720	BP2092	FC32 (trim 1/4") in base	OS20	1 1/4	546.9	ST Original-15 #7		8500	1100
221208-11597	20	Cheddite	Ched209 HOT	Lil' Gun	29.2	N720	BP2090 (slit)	FC32 (trim 1/4") in base	OS20	1 1/4	546.9	ST Original-15 #7		11450	1166
11597.2	20	Cheddite	Ched209 HOT	Lil' Gun	29.2	N720	BP2092	FC32 (trim 1/4") in base	OS20	1 1/4	546.9	ST Original-15 #7		10800	1160
180326-9935	20	Cheddite	Ched209	Lil' Gun	32.0		CSD203 (slit)	18FW20 in base		1 1/4	546.9	ST Original-15 #7		7705	1205
180412-9944	20	Cheddite	Ched209	Lil' Gun	32.0		CSD203 (slit)	14FW20 in base	OS20	1 3/8	601.6	ST Original-15 #7		11260	1260
11522	20	Fiocchi	Fio616	Lil' Gun	26.2	N720	BP2092	FC32 (trim 1/8") in base	OS20	1 3/8	601.6	ST Original-15 #7		10300	1076
11526	20	Fiocchi	Fio616	Lil' Gun	27.6	N720	BP2092	FC32 (trim 1/8") in base	OS20	1 3/8	601.6	ST Original-15 #7		8500	1065
10974	20	Fiocchi	Fio616	Lil' Gun	34.0	PT20GS	TPS2044 (slit)	18CW28 in base	OS20	1 3/8	601.6	ST Original-15 #7		10485	1240
180413-9951	20	Cheddite	Ched209	Lil' Gun	25.0	NC20	CSD203 (slit)	(2) NC28 in base		1 1/2	656.3	ST Original-15 #7		7685	1010



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER	PSI	FPS
28-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
10951	28	Cheddite	Ched209	Lil' Gun	28.0		TPS28	FC410 (cut in 1/2) in base	OS28	3/4	328.1	ST Original-15 #7		9560	1395
180222-9873	28	Cheddite	Ched209	Pro Reach	14.0		TPS28	(3) 14C41 in base	OS28	3/4	328.1	ST Original-15 #7		9700	1200
180326-9936	28	Cheddite	Ched209	Lil' Gun	25.0		TPS28	(2) 14C41 in base		13/16	355.5	ST Original-15 #7		7710	1270
11155	28	Cheddite	Ched209	Lil' Gun	26.0		TPS28	FC410 + NC410 in base	OS28	7/8	382.8	ST Original-15 #7		11473	1318
180222-9872	28	Cheddite	Ched209	Lil' Gun	28.0		TPS28	(2) 14C41 in base	OS28	7/8	382.8	ST Original-15 #7		11860	1415
10953	28	Cheddite	Ched209	Lil' Gun	23.5		TPS28	14C41 in base	OS28	1	437.5	ST Original-15 #7		11483	1202
.410-BORE • 3" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • ROLL CRIMP															
11099	410	Fiocchi	Fio616	H110	19.0		TPS410		OS410	9/16	246.1	ST Original-15 #7	10 gr Original	11693	1337
11103	410	Fiocchi	Fio616	Alliant 410	13.4		TPS410		OS410	5/8	273.4	ST Original-15 #7		11680	1146
11104	410	Fiocchi	Fio616	Lil' Gun	13.6		TPS410		OS410	5/8	273.4	ST Original-15 #7		9823	810
.410-BORE • 3" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP															
180413-9950	410	Cheddite	Ched209	Alliant 410	12.0		TPS410			5/8	273.4	ST Original-15 #7		11170	1190
180412-9947	410	Cheddite	Ched209	Lil' Gun	14.0		TPS410			5/8	273.4	ST Original-15 #7		12650	1215
180716-10087	410	Fiocchi	Fio616	Alliant 410	12.0		TPS410			5/8	273.4	ST Original-15 #7		7720	1090



WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER	PSI	FPS
10-GAUGE • 3-1/2" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • ROLL CRIMP															
11454	10	Cheddite	Ched209	Longshot	36.0	(2) X10X	BP1044	14FW12 in base + MYTHIN	OS10	1 1/2	656.3	ST Super Max-18 #5		8705	1295
11453	10	Cheddite	Ched209	Longshot	38.0	(2) X10X	BP1044	14FW12 in base + MYTHIN	OS10	1 1/2	656.3	ST Super Max-18 #5		9200	1318
12-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP															
180911-10623-7	12	Fiocchi	Fio616	Longshot	40.0		CSD078 (slit)	(2) 14CW20 in base		7/8	382.8	ST Super Max-18 #7		6395	1625
180911-10623-9	12	Fiocchi	Fio616	Longshot	40.0		CSD078 (slit)	(2) 14FW20 + 18FW20 in base		7/8	382.8	ST Super Max-18 #9		6395	1625
180830-10620	12	Fiocchi	Fio616	Universal	30.0	FS12	LBC30 (slit)	(2) 14FW20 in base		7/8	382.8	ST Super Max-18		7340	1400
180830-10621	12	Fiocchi	Fio616	Longshot	36.0	FS12	LBC30 (slit)	14FW20 + 18FW20 in base		1	437.5	ST Super Max-18		7500	1490
12-GAUGE • 3-1/2" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP															
180926-10649	12	Fiocchi	Fio616	Steel	36.0	FS12	MG42	18FW20 in base	OS12	2	875.0	ST Super Max-18		8980	1140
16-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP															
11132	16	Cheddite	Ched209	Steel	26.7		CSD16 (slit)	(2) 14FW20 + 14CW20 in base	OS16	3/4	328.1	ST Super Max-18 #7		7145	1380
11131	16	Cheddite	Ched209	Universal	22.2		CSD16 (slit)	(2) 14FW20 + 14CW20 in base		3/4	328.1	ST Super Max-18 #7		10008	1383
180911-10628	16	Fiocchi	Fio616	Pro Reach	26.0		CSD16 (slit)	(3) 14CW20 + 18FW20 in base		7/8	382.8	ST Super Max-18 #7		5745	1360
11540.2	16	Cheddite	Ched209	Blue Dot	26.3		BP1680 (slit)	(3) 14FW20 + 18CW28 in base	OS16	1 1/8	492.2	ST Super Max-18 #9		10700	1225
11540	16	Cheddite	Ched209	Blue Dot	26.8		BP1680 (slit)	(3) 14FW20 + 18CW28 in base	OS16	1 1/8	492.2	ST Super Max-18 #9		11000	1250
20-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP															
221214-11606	20	Cheddite	Ched209	Longshot	18.7	N720	BP2090 (slit)	FC32 + 18CW28 in base	OS20	1	437.5	ST Super Max-18 #9		11200	1157
221214-11601	20	Federal Top Gun	Ched209	Lil' Gun	27.4	N720	BP2090 (slit)	FC32 + 18CW28 in base	OS20	1	437.5	ST Super Max-18 #9		10800	1193
11254	20	Fiocchi	Fio616	Lil' Gun	27.2		TPS2044 (slit)	(5) 18CW28 in base	OS20	1 1/4	546.9	ST Super Max-18 #7		7900	1058
11261	20	Fiocchi	Fio616	Lil' Gun	37.0		TPS2044 (slit)	(5) 18CW28 in base	OS20	1 1/4	546.9	ST Super Max-18 #7		11300	1336
11262	20	Fiocchi	Fio616	Longshot	19.8		CSD20 (slit)	(5) 18CW28 in base	OS20	1 1/4	546.9	ST Super Max-18 #9		10845	1095
191226-10741	20	Fiocchi	Fio616	Lil' Gun	28.0		CSD20 (slit)		OS20	1 5/8	710.9	ST Super Max-18	12 gr Mix #47	10940	1095
28-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • ROLL CRIMP															
11246	28	Cheddite	Ched209	Lil' Gun	30.0		TPS28	(1.5) FC410 in base	OS28	7/8	382.8	ST Super Max-18 #9		11925	1389
230512-11835	28	Fiocchi	Fio616	Lil' Gun	30.0		TPS28	(1.5) FC410 in base	OS28	7/8	382.8	ST Super Max-18 #9		10300	1425
230515-11838	28	Fiocchi	Fio616	Lil' Gun	26.0		TPS28	(1.5) FC430 in base	OS28	1	437.5	ST Super Max-18 #9		7050	1150
230515-11837	28	Fiocchi	Fio616	Lil' Gun	27.0		TPS28	(1.5) FC430 in base	OS28	1	437.5	ST Super Max-18 #9		8040	1215



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER	PSI	FPS
28-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP															
191226-10788	28	Cheddite	Ched209	Lil' Gun	28.0		TPS28	(1.5) FC410 in base	OS28	3/4	328.1	ST Super Max-18	10 gr Mix #47	7260	1340
11156	28	Cheddite	Ched209	Lil' Gun	27.0		TPS28	FC410 + (2) NC410 in base	OS28	7/8	382.8	ST Super Max-18 #9		11065	1338
191226-10789	28	Cheddite	Ched209	Lil' Gun	28.0		TPS28	FC410 + (2) NC410 in base	OS28	7/8	382.8	ST Super Max-18	10 gr Mix #47	9140	1355
191226-11836	28	Cheddite	Ched209	Lil' Gun	30.0		TPS28	FC410 + (2) NC410 in base	OS28	7/8	382.8	ST Super Max-18		10200	1400
230512-11841	28	Fiocchi	Fio616	Lil' Gun	24.0		TPS28	(1.25) FC410 in base	OS28	1	437.5	ST Super Max-18 #9		6000	1100
230512-11839	28	Fiocchi	Fio616	Lil' Gun	25.0		TPS28	(1.25) FC410 in base	OS28	1	437.5	ST Super Max-18 #9		6500	1125
.410-BORE • 3" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • ROLL CRIMP															
11457	410	Cheddite	Ched209	Win. 296	13.6		TPS410	FC310 in base	OS410	11/16	300.8	ST Super Max-18 #9		7700	931
11458	410	Cheddite	Ched209	Win. 296	15.0		TPS410	FC310 in base	OS410	11/16	300.8	ST Super Max-18 #9		9100	1071
11043	410	Fiocchi	Fio616	H110	14.5		TPS410	FC310 in base	OS410	11/16	300.8	ST Super Max-18 #9		7315	1014
11456	410	Fiocchi	Fio616	H110	16.0		TPS410	FC310 in base	OS410	11/16	300.8	ST Super Max-18 #9		11798	1177
11045	410	Fiocchi	Fio616	Alliant 410	11.2		TPS410		OS410	13/16	355.5	ST Super Max-18 #9		12577	982
11049	410	Fiocchi	Fio616	H110	15.0		TPS410		OS410	13/16	355.5	ST Super Max-18 #9		10005	1030
11050	410	Fiocchi	Fio616	H110	16.0		TPS410		OS410	13/16	355.5	ST Super Max-18 #9		12648	1107
10823	410	Cheddite	Ched209	Alliant 300MP	15.5		TPS410		OS410		374.0	ST Super Max-18 #9		9860	1005
.410-BORE • 3" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP															
11193	410	Cheddite	Ched209	Alliant 410	14.5		TPS410	(2) FC310 in base		1/2	218.8	ST Super Max-18 #9		6600	1109
11189	410	Cheddite	Ched209	Lil' Gun	18.0		TPS410	(2) FC310 in base		1/2	218.8	ST Super Max-18 #9		12774	1431



WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

