



BPI LOAD GUIDE:

BP1044 DECI-MAX

WWW.BALLISTICPRODUCTS.COM

10GA 2-7/8" & 3-1/2" LEAD & NON-TOXIC SHOT WAD

The BP1044 is a light capacity 10ga wad with a volume-consuming cushion section. This wad adds great variety and usefulness to the 10ga. Our staff loves this wad for lighter and low-pressure loads for the 10ga. You'll like it too for some great nickel-plated lead, bismuth loads.

Curmudgeon's Loading Tips:

The BP1044 is ideal for light field loads and clay target practice. The BP1044 broadens the usefulness of the 10-gauge, combined with its pre-slit design, making for easy loading. A cushion section accepts loader pressure while accommodating various load heights, minimizing the need for filler wads.

Applications: The BP1044 is best suited for lead and bismuth loads in light-weight shot charges and small shot sizes. Do not use steel shot with this wad.



WAD SPECIFICATIONS:

- Overall length: 1.686"
- Shotcup depth: 0.976"
- Seal to cup bottom: 0.660"
- Product Type: Wad, Multi-Metal capable for field use. Pre-slit for easy loading.
- Typical Loads: Lead and non-toxic lightweight field loads.

Load ID	Ga.	Hull	Primer	Powder	Powder Grns.	Gas Seal	Wad	Filler Wads & Load Inserts	Over Shot	Shot (oz.)	Shot (grns.)	Shot Size	Buffer	PSI	FPS
10-GAUGE • 2-7/8" LENGTH • LEAD SHOT • ROLL CRIMP															
110718-3232R	10	Federal FB	Fed209A	Clays	24.0		BP1044	(2) 14FW12 in base	NC10	1	437.5	Lead		8000	1380
110718-3232	10	Federal FB	Fed209A	Clays	26.0		BP1044	(2) 14FW12 in base	NC10	1	437.5	Lead		9000	1450
110718-3233	10	Federal FB	Fed209A	Clays	28.0		BP1044	(2) 14FW12 in base	NC10	1	437.5	Lead		10400	1480
10-GAUGE • 3-1/2" LENGTH • LEAD SHOT • FOLD CRIMP															
150417-6425	10	Cheddite	Ched209	Pro Reach	40.0	X10X + NC10	BP1044		OS10	1 1/2	656.3	Lead #T/BB		9500	1410
150422-6447	10	Cheddite	Ched209	Pro Reach	42.0	X10X	BP1044	18FW12 in wad	OS10	1 1/2	656.3	Lead #T/BB		9700	1430
170203-9222	10	Cheddite	Ched209	Pro Reach	40.0	X10X	BP1044		OS10	1 5/8	710.9	Lead #2		9200	1400
170215-9237	10	Cheddite	Ched209	Longshot	34.0	X10X	BP1044		OS10	1 7/8	820.3	Lead #2		6600	1150
170215-9252	10	Cheddite	Ched209	HS-6	38.0	X10X	BP1044			2	875.0	Lead #2		8400	1175
170203-9211	10	Federal FB	Fed209A	Longshot	33.0		BP1044	18FW12 in wad	OS10	2 1/4	984.4	Lead #2		9600	1125
10-GAUGE • 3-1/2" LENGTH • BISMUTH SHOT • FOLD CRIMP															
11637	10	Cheddite	Ched209	Longshot	42.3	X10X	BP1044	18FW12 in base	OS12	1 3/8	601.6	Bismuth #BB	20 gr Original	9200	1435
11618.2	10	Cheddite	Ched209	Longshot	43.0	X10X	BP1044	18FW12 in base	OS10	1 3/8	601.6	Bismuth #BB	20 gr Original	10200	1475
11638	10	Cheddite	Ched209	HS-6	41.5	X10X	BP1044	18FW12 in base	OS10	1 5/8	710.9	Bismuth #BB	20 gr Original	10800	1300
11471	10	Cheddite	Ched209	Blue Dot	37.0	X10X	BP1044		OS10	1 3/4	765.6	Bismuth	20 gr Original	6733	1114
11636	10	Cheddite	Ched209	Blue Dot	39.0	NC10	BP1044		OS10	1 3/4	765.6	Bismuth #BB	20 gr Original	7900	1190
10-GAUGE • 3-1/2" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • ROLL CRIMP															
11454	10	Cheddite	Ched209	Longshot	36.0	(2) X10X	BP1044	14FW12 in base + MYTHIN	OS10	1 1/2	656.3	ST Super Max-18 #5		8705	1295
11453	10	Cheddite	Ched209	Longshot	38.0	(2) X10X	BP1044	14FW12 in base + MYTHIN	OS10	1 1/2	656.3	ST Super Max-18 #5		9200	1318

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".