



# BPI COMPONENT GUIDE: SPITFIRE

WWW.BALLISTICPRODUCTS.COM

The Spitfire is a great 7/8 to 1 ounce performance wad. Try it with some quick-hitting clays or dove loads. The optimum range is 25 - 55 yards and is best utilized for mid-range utility loads and high-speed load production

“★★★★★ - **Very Nice Wads!** I have used these with my Cheddite hulls loading on my MEC press. ZERO PROBLEMS and I have used a little over a thousand so far. Easy loading. I have to get more and stock up.” - Eric, NY

“★★★★★ - **trap shooting** This wad works excellent with Green Dot powder. Patterns are very consistent and recoil is reduced. Have compared to other brand wads with same charge and this is the clear winner. On paper or at the range I think you will be happy with the results.”

## RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and research- i n g . Don't try to outsmart the instructions! We offer over a half century of loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and “Load of the Week” at [www.ballisticproducts.com](http://www.ballisticproducts.com)**



### TECHNICAL SPECS:

OVERALL LENGTH:	1.660"
DIAMETER:	0.725"
SHOTCUP DEPTH:	0.720"
SEAL TO CUP BOTTOM:	0.940"
THICKNESS:	0.025"



LD12SF12



**WARNING**

Cancer and Reproductive Harm  
- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
12-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP															
141114-6122-8	12	Cheddite	Ched209	W S Handicap	28.0		SPITFIRE		0S12	3/4	328.1	Lead #8		9800	1615
141114-6122X8	12	Cheddite	Ched209	W S Handicap	28.0		SPITFIRE	X-Stream Spreader	0S12	3/4	328.1	Lead #8		9800	1615
140411-5603	12	Cheddite	Ched209	700-X	19.0		SPITFIRE		0S12	7/8	382.8	Lead #8		9200	1330
140411-5598	12	Cheddite	Ched209	Clays	18.0		SPITFIRE		0S12	7/8	382.8	Lead #8		8200	1225
140416-5634	12	Cheddite	Ched209	Red Dot	20.0		SPITFIRE			7/8	382.8	Lead #7.5		9300	1320
10908-908T	12	Fiocchi	Win209	Bullseye	22.0	BPGS	SPITFIRE		0S12	7/8	382.8	Lead #8		9000	1230
140411-5606	12	Cheddite	Ched209	700-X	19.0		SPITFIRE			1	437.5	Lead #8		9500	1275
140411-5602	12	Cheddite	Ched209	Clays	18.0		SPITFIRE			1	437.5	Lead #8		8900	1190
140411-5596	12	Cheddite	Ched209	International	22.0		SPITFIRE			1	437.5	Lead #8		8500	1230
140416-5636	12	Cheddite	Ched209	W S Handicap	24.0		SPITFIRE			1	437.5	Lead #7.5		9800	1375
90316-587SF	12	Fiocchi	Fio616	Green Dot	22.1		SPITFIRE			1	437.5	Lead #8		8800	1290

## OTHER USEFUL COMPONENTS



**20GA 1/8" CORK WADS**  
18CW20 | #1222820




**20GA 1/4" CORK WADS**  
14CW20 | #1222420



**20GA 1/8" FELT WADS**  
18FW20 | #1221820



**20GA 1/4" FELT WADS**  
14FW20 | #1221420



**12GA OVERSHOT CARDS**  
0S12 | #0S 12

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. **We recommend 20 gauge felt or cork fillers for inside the 12 gauge wads.**

**WARNING:** BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.