



BPI LOAD GUIDE:

BP1680 STRIKER

WWW.BALLISTICPRODUCTS.COM

16GA MULTI-METAL WAD

The BP1680 Striker is manufactured with our toughest TPS molding resin. It is the toughest and sturdiest 16ga wad on the planet. It is designed with Multi-Metal capabilities to accommodate heavy payloads in 16 gauge field loads. Our ballistic lab is producing all-new load data for the BP1680 that will include lead, steel, bismuth, BPX-12, SpheroTungsten 15.0, and SpheroTungsten 18.0. (Load data for the original PT1680 wad do not apply to the BP1680 Striker).

Slitting: The BP1680 is an unslit shotcup. The handloader MUST slit this wad before loading. Three to four slits of a minimum depth of 80% of the total length of the wad are required. Failure to slit the wad will produce a potentially dangerous slug-type projectile. (A preslit version is coming soon.)

MADE IN USA

STRIKER BP1680

*Dimensions

| | |
|-----------------|-------------|
| Overall Length: | 1.625" |
| Shotcup Depth: | 1.413" |
| Gas Seal Diam: | 0.670" |
| Gas Seal Depth: | 0.085" |
| Cushion Height: | NA |
| Weight: | 37.0 grains |

Features

- Maximum-capacity 16ga field wad
- Varied load payloads and shot types.
- Unslit for custom slitting



| LOAD ID | GA. | HULL | PRIMER | POWDER | POWDER GRNS. | GAS SEAL | WAD | FILLER WADS & LOAD INSERTS | OVER SHOT | SHOT (OZ.) | SHOT (GRNS.) | SHOT SIZE | BUFFER (GRAINS) | PSI | FPS |
|---|-----|----------|---------|-----------|--------------|----------|--------|----------------------------|-----------|------------|--------------|-----------|-----------------|-------|------|
| 16-GAUGE • 2-3/4" LENGTH • BISMUTH SHOT • FOLD CRIMP | | | | | | | | | | | | | | | |
| 11534 | 16 | Cheddite | Ched209 | Longshot | 20.8 | | BP1680 | 14FW20 | OS16 | 7/8 | 382.8 | #5 | | 8825 | 1255 |
| 11547.2 | 16 | Cheddite | Ched209 | Steel | 22.6 | | BP1680 | | OS16 | 1 1/8 | 492.2 | #5 | 12 grains Orig. | 10700 | 1199 |
| 16-GAUGE • 2-3/4" LENGTH • BPX-12 DEVASTATOR SHOT • FOLD CRIMP | | | | | | | | | | | | | | | |
| 11546 | 16 | Cheddite | Ched209 | Longshot | 21.8 | N716 | BP1680 | (2) 14FW20 | OS16 | 1 | 437.5 | #6 | | 10900 | 1255 |
| 11545 | 16 | Cheddite | Ched209 | Longshot | 23.8 | N716 | BP1680 | (2) 14FW20 | OS16 | 1 | 437.5 | #6 | | 10160 | 1367 |
| 11543 | 16 | Fiocchi | Fio616 | Longshot | 20.0 | N716 | BP1680 | (2) 14FW20 | OS16 | 1 | 437.5 | #6 | | 8700 | 1168 |
| 16-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN ORIGINAL-15 SHOT • FOLD CRIMP | | | | | | | | | | | | | | | |
| 11531 | 16 | Cheddite | Ched209 | Blue Dot | 22.2 | | BP1680 | (2) 14FW20 + 18CW28 | OS16 | 1 1/8 | 492.2 | #7 | | 6198 | 1017 |
| 11532 | 16 | Cheddite | Ched209 | Blue Dot | 24.6 | | BP1680 | (2) 14FW20 + 18CW28 | OS16 | 1 1/8 | 492.2 | #7 | | 7343 | 1111 |
| 11542 | 16 | Cheddite | Ched209 | Blue Dot | 27.8 | | BP1680 | (2) 14FW20 + 18CW28 | OS16 | 1 1/8 | 492.2 | #7 | | 10800 | 1286 |
| 11541 | 16 | Fiocchi | Fio616 | Blue Dot | 26.0 | | BP1680 | (2) 14FW20 + 18CW28 | OS16 | 1 1/8 | 492.2 | #7 | | 10900 | 1223 |
| 16-GAUGE • 2-3/4" LENGTH • SPHEROTUNGSTEN SUPER MAX-18 SHOT • FOLD CRIMP | | | | | | | | | | | | | | | |
| 11540.2 | 16 | Cheddite | Ched209 | Blue Dot | 26.3 | | BP1680 | (3) 14FW20 + 18CW28 | OS16 | 1 1/8 | 492.2 | #9 | | 10700 | 1225 |
| 11540 | 16 | Cheddite | Ched209 | Blue Dot | 26.8 | | BP1680 | (3) 14FW20 + 18CW28 | OS16 | 1 1/8 | 492.2 | #9 | | 11000 | 1250 |
| 16-GAUGE • 2-3/4" LENGTH • STEEL SHOT • FOLD CRIMP | | | | | | | | | | | | | | | |
| 11552 | 16 | Cheddite | Ched209 | Universal | 18.6 | | BP1680 | 14FW20 + 18CW28 | OS16 | 3/4 | 328.1 | #5 | | 9800 | 1246 |
| 11551 | 16 | Cheddite | Ched209 | Universal | 19.9 | | BP1680 | 14FW20 + 18CW28 | OS16 | 3/4 | 328.1 | #5 | | 10800 | 1352 |
| 11529 | 16 | Cheddite | Ched209 | Steel | 25.5 | | BP1680 | 18CW28 | OS16 | 7/8 | 382.8 | #5 | | 10600 | 1397 |

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".