



BPI COMPONENT GUIDE:

SPORTING 16

WWW.BALLISTICPRODUCTS.COM

Original Sporting 16 wad offers the optimum volume for classic sixteen gauge performance. Of course, we can load more, but 7/8 to 1 oz loads just give us that ideal match between bore diameter and payload height. This affordable wad allows you to shoot your sixteen more often.

Identifying feature: Note the 24 pins that protrude down from the gas seal in a two circular designs around one central pin. These pins occupy space that would otherwise be filled with propellant, thus lifting the wad above the propellant charge.

Wad design: Tear-away petal design, G-ring crush section, and an exceptional gas seal, creating consistent and clean-burning loads. Recommended as a superior pheasant and dove wad.

“★★★★★ - **Exceptional all around wad** I have used this wad for low pressure loads for skeet, clays and dove hunting with exceptional results in my Vintage double guns. When loaded in Fiocchi hulls with Unique powder and 1 oz. shot. I have experienced consistent, very effective patterns with mild recoil.” - Buddy, GA

RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of



loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and “Load of the Week” at www.ballisticproducts.com**



TECHNICAL SPECS:

OVERALL LENGTH:	1.440"
DIAMETER:	0.665"
SHOTCUP DEPTH:	0.655"
SEAL TO CUP BOTTOM:	0.785"
THICKNESS:	0.027"



LD16SG16




WARNING

Cancer and Reproductive Harm
- www.P65Warnings.ca.gov


LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
16-GAUGE • 2-1/2" LENGTH • LEAD SHOT • ROLL CRIMP															
11127.1	16	Cheddite	Ched209	Titewad	14.8		SG16		OS16	7/8	382.8	Lead		10840	1168
16-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP															
90720-1038R	16	Cheddite	Ched209	Green Dot	24.0	NC16	SG16			5/8	273.4	Lead #9		9000	1600
90720-1043	16	Fiocchi	Fio616	Titewad	20.0	NC16	SG16			5/8	273.4	Lead #9		10000	1580
100412-1988R	16	Cheddite	Ched209	Universal	27.0	NC16	SG16			3/4	328.1	NP Lead #6		9900	1585
90803-1106	16	Fiocchi	Fio616	Green Dot	25.0		SG16			3/4	328.1	Lead #8		10500	1600
130325-4667	16	Cheddite	Ched209	Alliant 20/28	26.0		SG16		OS16	7/8	382.8	NP Lead #6		10300	1565
100226-1802	16	Cheddite	Ched209	Longshot	29.0		SG16		OS16	7/8	382.8	Lead #7.5		8800	1480
100219-1768	16	Fiocchi	Fio616	Herco	22.5		SG16			7/8	382.8	Lead #7.5		9200	1390
90908-1293R	16	Cheddite	Ched209	Alliant 20/28	22.0		SG16			1	437.5	Lead #7		8700	1310
50214-661RL	16	Fiocchi	Ched209	Unique	22.0		SG16		OS16	1	437.5	Lead		11000	1375
16-GAUGE • 2-3/4" LENGTH • BISMUTH SHOT • FOLD CRIMP															
171005-9643	16	Cheddite	Ched209	Green Dot	20.0		SG16			7/8	382.8	Bismuth #5		9000	1345

OTHER USEFUL COMPONENTS

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. We recommend 20ga felt fillers for inside the 16 gauge wads.



16GA 1/8" MAXI-NITRO CARD
NC16 | #NC16



16GA OVERSHOT CARDS
OS16 | #OS16



20GA 1/8" FELT WADS
18FW20 | #1221820



20GA 1/4" FELT WADS
14FW20 | #1221420

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.