



BPI COMPONENT GUIDE:

SPORTING 16 SHORT

WWW.BALLISTICPRODUCTS.COM

By popular demand we've added the Sporting Sixteen Short wad to our stock line of 16ga wads. This wad is dimensionally the same as the original Sporting Sixteen except for the gas seal, which is open and concave. The result of this design difference means that powder fills the gas seal and the Sporting Sixteen Short wad sits about 3mm (about 1/8") lower than the original Sporting Sixteen. Sporting Sixteen Short is better for bulkier powders, heavier shot charges or large pellet sizes.

Now you have two different versions of the Sporting Sixteen for your favorite loads. This affordable wad allows you to shoot your sixteen more.

Identifying feature: Note six pegs that protrude down from the gas seal in a circular design (see image right).

Wad design: Tear-away petal design, G-ring crush section, and an exceptional gas seal, creating consistent and clean-burning loads. The Sporting 16 is recommended as a superior pheasant and dove wad.

RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of

loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and "Load of the Week" at www.ballisticproducts.com**



TECHNICAL SPECS:

OVERALL LENGTH:	1.440"
DIAMETER:	0.665"
SHOTCUP DEPTH:	0.655"
SEAL TO CUP BOTTOM:	0.785"
THICKNESS:	0.027"



LD16SG16S



WARNING


Cancer and Reproductive Harm
- www.P65Warnings.ca.gov

LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
16-GAUGE • 2-1/2" LENGTH • BISMUTH SHOT • ROLL CRIMP															
11556.2	16	Cheddite	Ched209	International	18.0		SG16S		OS16	3/4	328.1	Bismuth	15gr BSB	7650	1257
16-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP															
130325-4669	16	Cheddite	Ched209	Alliant 20/28	24.0		SG16S		OS16	7/8	382.8	NP Lead #6		9500	1480
130103-4483	16	Cheddite	Ched209	Universal	24.0		SG16S		OS16	7/8	382.8	Lead #8		10800	1480
130103-4495	16	Cheddite	Ched209	Green Dot	20.0		SG16S			1	437.5	Lead #8		10700	1310
130103-4492	16	Cheddite	Ched209	Unique	20.0		SG16S			1	437.5	Lead #8		9200	1240

OTHER USEFUL COMPONENTS



16GA 1/8" MAXI-NITRO CARD
NC16 | #NC 16



16GA OVERSHOT CARDS
OS16 | #OS 16



20GA 1/8" FELT WADS
18FW20 | #1221820



20GA 1/4" FELT WADS
14FW20 | #1221420

Nitro cards are used as a seal or spacer between the powder and the plastic wad or directly underneath shot. Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. **We recommend 20ga felt fillers for inside the 16 gauge wads.**

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.