



## BPI COMPONENT GUIDE:

# Z16 FIELD COMMANDER

WWW.BALLISTICPRODUCTS.COM

When loaded with 1-1/8 oz of nickel-plated shot, the Z16 Commander is truly a proven field performer. An easy-loading, compact wad that is great for both field and target. The shot capacity is just a bit larger than the standard 16-gauge wad because it is designed for longer ranges. Like the 12-gauge Z21 Trap Commander, the Z16's cushion section allows for a final "nudge" as the shell is closed, so loads are compressed for a solid ignition and consistency.

Designed for heavy 1-1/8 and even 1-1/4 oz loads, but it can be loaded down to 7/8oz by lightly seating the wad and using fillers.

"★★★★★ - **Wow!** I am impressed with this wad. I did a lot of pattern testing. 3 loads actually had identical pellet counts on the targets! Amazing consistency!" - M.M., AZ

## RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of



loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and "Load of the Week" at [www.ballisticproducts.com](http://www.ballisticproducts.com)**



### TECHNICAL SPECS:

OVERALL LENGTH:	1.500"
DIAMETER:	0.665"
SHOTCUP DEPTH:	0.690"
SEAL TO CUP BOTTOM:	0.810"
THICKNESS:	0.040"



LD16Z16




**WARNING**


Cancer and Reproductive Harm  
- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
<b>16-GAUGE • 2-1/2" LENGTH • LEAD SHOT • ROLL CRIMP</b>															
150819-7068	16	Cheddite	Ched209	Red Dot	16.0		Z16		OS16	1	437.5	Lead #7.5		10600	1170
<b>16-GAUGE • 2-1/2" LENGTH • BISMUTH SHOT • ROLL CRIMP</b>															
180508-9988	16	Cheddite	Ched209	Longshot	25.0		Z16		OS16	7/8	382.8	Bismuth #5/6/7		7040	1420
<b>16-GAUGE • 2-3/4" LENGTH • LEAD SHOT • ROLL CRIMP</b>															
170724-9530	16	Fiocchi	Fio616	Green Dot	20.0		Z16		OS16	7/8	382.8	Lead #5		9000	1350
180514-10004	16	Cheddite	Ched209	Longshot	28.0		Z16		OS16	1	437.5	Lead #6/#7		8595	1465
<b>16-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP</b>															
180405-9938	16	Cheddite	Ched209	Pro Reach	29.0		Z16		OS16	7/8	382.8	Lead #5		10740	1535
100226-1814B	16	Cheddite	Ched209	Longshot	27.0		Z16		OS16	1	437.5	Lead #7.5		9600	1400
131113-5268	16	Cheddite	Ched209	Unique	22.0		Z16			1 1/16	464.8	Lead #6		9800	1260
180509-9994	16	Cheddite	Ched209	Herco	22.0		Z16			1 1/8	492.2	NP Lead # 4/5/6		9070	1270
140124-5412	16	Fiocchi	Fio616	Longshot	26.0		Z16		OS16	1 1/8	492.2	Lead #5		9800	1340
101007-2523	16	Cheddite	Ched209	Longshot	24.0		Z16			1 1/4	546.9	Lead #4/5/6		10000	1260

## OTHER USEFUL COMPONENTS



**16GA 1/8" MAXI-NITRO CARD**  
NC16 | #NC16



**16GA OVERSHOT CARDS**  
OS16 | #OS16



**20GA 1/8" FELT WADS**  
18FW20 | #1221820



**20GA 1/4" FELT WADS**  
14FW20 | #1221420

Nitro cards are used as a seal or spacer between the powder and the plastic wad or directly underneath shot. Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. We recommend 20ga felt fillers for inside the 16 gauge wads.

**WARNING:** BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

**ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.**