



**BPI LOAD GUIDE:**

# 20GA TC VITAL-SHOK SABOTS

[WWW.BALLISTICPRODUCTS.COM](http://WWW.BALLISTICPRODUCTS.COM)

## 20GA TROPHY COPPER VITAL-SHOK SABOT

Our VALU-SLUGS come from a major U.S. cartridge manufacturer. They are contained and sorted by size through a rigid demil<sup>1</sup> process. BPI is offering these slugs in box quantities to maximize savings for our customers.

### SABOT & BULLET SPECIFICATIONS:

- Bullet Dimensions: 0.500" x 1.063" lead hollow point (279 gains)
- Sabot Weight: 38 grains (w/aluminum backing plate)
- Total Weight: 317 grains (bullet + sabot)
- Product Type: Lead sabot slug
- NOTE: These are approximate weights and sizes (actual measurements may vary.) Acceptable industry tolerances apply; expect slight variances in shot counts and diameters due to production differences.

<sup>1</sup> De-Mil materials: This means that these components have been extracted from manufactured cartridges. The company that performs this action acknowledges that imperfections can and do exist in these components. This is why they are priced very aggressively. If you require perfect components, please look at our specific departments for newly-manufactured components.



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	PROJECTILE	OVER SHOT	SLUG & SABOT WEIGHT (OUNCES)	SLUG & SABOT WEIGHT (GRAINS)	PSI	FPS
20-GAUGE • 2-3/4" LENGTH • TROPHY COPPER SABOT SLUG • ROLL CRIMP														
220323-11213.1	20	Cheddite	Ched209	Longshot	21.4		SG20M (no petals)		TROPHY COPPER VITAL-SHOK		3/4 (approx.)	317	11400	1376
230502-11815	20	Federal	Fed209A	HS-6	23.0		SG20S (no petals)		TROPHY COPPER VITAL-SHOK		3/4 (approx.)	317	10492	1413
230502-11811.2	20	Federal	Fed209A	Pro Reach	22.5		SG20S (no petals)		TROPHY COPPER VITAL-SHOK		3/4 (approx.)	317	11460	1600

**WARNING:** BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS, TESTING REPORTS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL, AND WE DISCLAIM ANY SUCH WARRANTIES. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".