



BPI COMPONENT GUIDE:

SPORTING 20 LONG

WWW.BALLISTICPRODUCTS.COM

The SG20-L is an extended length wad designed to accommodate denser types of powders, smaller shot payloads and/or large capacity, straight-walled hulls.

The cushion section of the SG20-L is comprised of a large tubular reducer that accommodates many different load heights and offers excellent inertia absorption during the firing process. The SG20-L's distinctively long configuration makes it an excellent choice for fast 3/4-ounce loads. These light recoil loads are the perfect solution for recoil-sensitive shooters.

PREFERRED APPLICATIONS:

- Optimum range: 20-50 yards
- Mid-range utility loads
- High speed load production
- Going-away targets

RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of loading knowledge, wit, and wisdom in our publications.



Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and "Load of the Week" at www.ballisticproducts.com**



TECHNICAL SPECS:

OVERALL LENGTH:	1.525"
DIAMETER:	0.610"
SHOTCUP DEPTH:	0.750"
SEAL TO CUP BOTTOM:	0.775"
THICKNESS:	0.025"



LD20SG20L



WARNING


Cancer and Reproductive Harm
- www.P65Warnings.ca.gov

LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
20-GAUGE • 2-1/2" LENGTH • LEAD SHOT • ROLL CRIMP															
60919-73	20	Fiocchi	Fio616	Longshot	24.0		SG20L		N720	7/8	382.8	Lead		9600	1420
20-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP															
91022-1495	20	Federal FB	Fed209A	Universal	21.5		SG20L			3/4	328.1	Lead #9		10100	1460
110509-3028	20	Fiocchi	Fio616	Universal	21.0		SG20L			3/4	328.1	Lead #8.5		10500	1500
90211-438	20	Remington Premier	Rem209P	Universal	18.0		SG20L			3/4	328.1	Lead #8		10000	1330
110916-3399	20	Winchester AA HS	Win209	Green Dot	14.5		SG20L			3/4	328.1	Lead #8		10300	1255
100803-2246A	20	Cheddite	Ched209	International	16.0		SG20L			7/8	382.8	NP Lead #8		9600	1220
140416-5611	20	Cheddite	Ched209	Unique	16.5		SG20L			7/8	382.8	Lead #7.5		8800	1145
100803-2346	20	Fiocchi	Fio616	International	16.0		SG20L			7/8	382.8	NP Lead #8		9500	1220
20-GAUGE • 3" LENGTH • LEAD SHOT • FOLD CRIMP															
221028-11462.1	20	Cheddite	Ched209	Longshot	22.6	NC20	SG20L		OS20	1	437.5	Lead #6		11700	1301

OTHER USEFUL COMPONENTS



20GA 1/8" MAXI-NITRO CARD
NC20 | #NC20



20GA OVERSHOT CARDS
OS20 | #OS20



32GA 1/4" CORK WADS
14CW32 | #14CW32



20GA 1/8" FELT WADS
18FW20 | #1221820



20GA 1/4" FELT WADS
14FW20 | #1221420

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. **We recommend 32ga cork or 20ga felt fillers for inside the 20 gauge wads (felt is soft and can be forced into the base of the wad).**

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.