



BPI COMPONENT GUIDE:

SPORTING 28-II SUPER

WWW.BALLISTICPRODUCTS.COM

The SG28-II is an updated model of the SG28 wad that has been a favorite of European field shooters for many years. It is designed to load 5/8 oz to 7/8 oz loads. The progressive crush section allows this wad to be loaded in either 2-3/4" or 2-1/2" cases. This is a great wad for long-range 28 gauge shooters. We have also used this wad to great advantage in sporting clays events. The best range for this wad is approximately 25 to 55 yards.

We suggest light loads of fine shot, #8-1/2 to #9. Most of our loads are 3/4 ounce. Fine small shot encourages maximum coverage in a smallbore pattern.

"★★★★★ - **SPORTING 28-II WAD** Awesome wad! It is very versatile from grouse to pheasants there is a load with this wad for it. High velocity 3/4 oz. loads are amazing with this wad." - PA

"★★★★★ - **28ga Sporting 28II Super Wads** Great wads. Been loading 7/8 oz. #7 for huns and chukars and it kills them quick and clean. Patterns amazing with light modified and improved modified in my O/U. Highly recommended." - Landon, ID

RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and "Load of the Week" at www.ballisticproducts.com**



TECHNICAL SPECS:

OVERALL LENGTH:	1.453"
DIAMETER:	0.550"
SHOTCUP DEPTH:	0.880"
SEAL TO CUP BOTTOM:	0.575"
THICKNESS:	0.035"



LD28SG28II



WARNING

Cancer and Reproductive Harm
- www.P65Warnings.ca.gov


LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
28-GAUGE • 2-1/2" LENGTH • LEAD SHOT • ROLL CRIMP															
101115-2570	28	Fiocchi	Fio616	Longshot	14.0		SG28-II		NC28	3/4	328.1	NP Lead #6.5		9300	1160
28-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP															
120427-3809	28	Cheddite	Ched209	Lil' Gun	37.0		SG28-II	NC410 in base		5/8	273.4	Lead		10700	1760
120430-3810	28	Fiocchi	Fio616	Lil' Gun	37.0		SG28-II	NC410 in base		5/8	273.4	Lead		8800	1675
180522-10021	28	Cheddite	Ched209	Lil' Gun	34.0		SG28-II			3/4	328.1	Lead #4/5/6		10585	1650
230607-11876	28	Cheddite	Ched209	Longshot	16.5		SG28-II		0S28	3/4	328.1	Lead #7.5		9930	1315
100913-2469-6	28	Fiocchi	Fio616	Steel	25.0		SG28-II		(2) 0S28	3/4	328.1	Np Lead #6		11000	1560
130826-4981	28	Cheddite	Ched209	Pro Reach	14.0		SG28-II			7/8	382.8	Lead #8		11300	1170
90820-1204	28	Fiocchi	Fio616	Lil' Gun	30.0		SG28-II			7/8	382.8	Lead		10500	1435
28-GAUGE • 2-3/4" LENGTH • BISMUTH SHOT • FOLD CRIMP															
171206-9727	28	Cheddite	Ched209	Lil' Gun	34.0		SG28-II			5/8	273.4	Bismuth #5		6885	1585
171213-9740	28	Cheddite	Ched209	Steel	23.0		SG28-II			5/8	273.4	Bismuth #5		11580	1670
10959	28	Fiocchi	Fio616	Longshot	14.5		SG28-II			3/4	328.1	Bismuth	10gr Original	10530	1224

OTHER USEFUL COMPONENTS

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. We recommend .410 & .430 Bore fillers for inside the 28 gauge wads.



28GA 1/8" MAXI-NITRO CARD
NC28 | #NC 28



28GA OVERSHOT CARDS
0S28 | #0S 28



.410 1/2" FIBER WAD
FC410 | #FC 410
.430 1/2" FIBER WAD
FC430 | #FC 430

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.