



**BPI LOAD GUIDE:**

# LOADING 12GA VALU-SLUGS

[WWW.BALLISTICPRODUCTS.COM](http://WWW.BALLISTICPRODUCTS.COM)

Our VALU-SLUGS come from a major U.S. cartridge manufacturer. They are contained and sorted by size through a rigid demilitarization process\*. BPI is offering these slugs in box quantities to maximize savings for our customers.

## 12ga Valu-Slug RSS305 Trophy Copper Sabot Technical Specs:

**Bullet Dimensions:** .50" x 1.110" (305 grains)

**Sabot Dimensions:** .725" x 1.115" (65 grains)

**Total Weight (bullet + sabot):** 370 grains

**Size:** NOTE - These are approximate weights and sizes. Actual measurements may vary.

## 12ga Valu-Sabot Power Shock Sabot 481 gr. Technical Specs:

**Bullet Dimensions:** .50" x .890" lead hollow-point (424 grains)

**Sabot Weight:** 57 grains

**Total Weight (bullet + sabot):** 481 grains

**Size:** NOTE - These are approximate weights and sizes. Actual measurements may vary.

\* **De-Mil materials:** This means that these components have been extracted from manufactured cartridges. The company that performs this action acknowledges that imperfections can and do exist in these components. This is why they are priced very aggressively. If you require perfect components, please look at our specific departments for newly-manufactured components.

## Valu-Sabot 305gr Slug



## Power Shock Sabot



**WARNING:** ALL SLUG BARRELS ARE NOT EQUAL. SOME SLUG BARRELS ARE MADE TOO LIGHT AND TOO THIN FOR USE WITH CERTAIN SLUG OR SABOT LOADS. IF YOUR SLUG BARREL IS THIN (.040" - .060") AT THE MUZZLE OR ANYWHERE ELSE (USE A MICROMETER) WE SUGGEST YOU DO NOT USE THE BARREL. (FOR INSTANCE, A VERY STRONG MOSSBERG SLUG BARREL RECENTLY MEASURED, BOASTS .110" THICKNESS - ALMOST THREE TIMES THE THICKNESS OF IMPORTED LIGHTWEIGHT SLUG BARRELS.)

**WARNING:** SPIRE TIP SLUGS PLACED WITHIN A TUBE MAGAZINE (I.E. PUMP OR AUTO SHOTGUNS) MUST NOT HAVE ANY PROTRUSIONS FROM THE CRIMP. ALTHOUGH IT IS UNLIKELY, IT IS POSSIBLE THAT THE TIP OF THE PROTRUDING SLUG COULD IMPACT THE PRIMER OF THE SHELL IN FRONT OF IT. THIS COULD BE EXTREMELY DANGEROUS. A POINTED SLUG SHOULD BE COVERED WITH A CARDBOARD OR PLASTIC DISC OR EVEN FOLD-CRIMPED. FAILING THAT, THE SHOTGUNNER SHOULD ONLY PLACE ONE SLUG AT A TIME IN A TUBE MAGAZINE. VERIFY NO SLUG, REGARDLESS OF TYPE, PROTRUDES PAST THE TOP OF A HULL.

Load ID	Ga.	Hull	Primer	Powder	Powder Grains	Gas Seal	Filler Wads & Load Inserts	Sabot	Projectile	Over Shot	Slug Wgt. (grains)	Total Wgt. (grains)	PSI	FPS
<b>12-Gauge • 2¾" Length • 305gr Trophy Copper Sabot Slug • Roll Crimp</b>														
11088	12	Federal	Fed209A	International	25.1		BRP-12	RSS305 Valu-Sabot	Trophy Copper Sabot Slug		305 grains	370 grains	11013	1555
11085	12	Fiocchi	Fio616	International	24.7	F512		RSS305 Valu-Sabot	Trophy Copper Sabot Slug		305 grains	370 grains	10010	1540
11086	12	Fiocchi	Fio616	Longshot	36.0	X12X	14FW12 + 38W12	RSS305 Valu-Sabot	Trophy Copper Sabot Slug		305 grains	370 grains	10615	1741
<b>12-Gauge • 2¾" Length • 481gr Power Shock Sabot • Roll Crimp</b>														
11089	12	Federal	Fed209A	Longshot	31.5		BRP-12	Power Shock Sabot	Lead Hollow Point Slug		424 grains	481 grains	9032	1440
11082.1	12	Fiocchi	Fio616	Green Dot	26.1		BRP-12	Power Shock Sabot	Lead Hollow Point Slug		424 grains	481 grains	10865	1400
11084	12	Fiocchi	Fio616	HS-6	33.0	X12X	14FW12 + 38W12	Power Shock Sabot	Lead Hollow Point Slug		424 grains	481 grains	10443	1358
11078	12	Fiocchi	Fio616	Pro Reach	29.1	F512		Power Shock Sabot	Lead Hollow Point Slug		424 grains	481 grains	9100	1570

**WARNING:** WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS, TESTING REPORTS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL, AND WE DISCLAIM ANY SUCH WARRANTIES. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".